



## Request for Extension to Grease Trap Cleaning Frequency

A. Grease traps must be cleaned at the required frequency for two cycles before submitting a request for extension. After two cleaning cycles are complete, a facility may request an extension to the cleaning frequency if **one (1)** of the following conditions is met. Extensions may be revised if they are not sufficient to maintain grease trap efficiency.

Condition 1	The owner/operator has demonstrated the grease trap will produce an effluent with no visible grease, <u>and</u> can demonstrate consistent compliance with BOD, TSS, FOG, & pH limits for the City of Abilene FOG Program.	Condition Met?	
		Yes	No
Documentation	A copy of the laboratory report for <u>each</u> of the two cleaning cycles must be included with this request form.		

Condition 2	Grease layer + solids layer must be less than 25% of total depth of trap contents. Generally, this occurs when the grease (top) layer is less than: a.) 5-6 inches deep for traps larger than 50 gals, b.) 2-3 inches deep for traps 50 gals or smaller.	Condition Met?	
		Yes	No
Documentation	A photograph from <u>each</u> of the two cleaning cycles which shows the depth of the grease layer with a legible scale.		

B. Complete this section only if one of the Conditions in Part A has been met and documented.

Facility Name				Facility Phone		
Facility Address						
Facility Business Hours	M: _____ - _____	T: _____ - _____	W: _____ - _____	Th: _____ - _____		
	F: _____ - _____	Sa: _____ - _____	Su: _____ - _____	Seasonal/Irregular		
Grease Trap Size	More than 50 gal	50 gal or less	How Old?			
Grease Trap Location	Inside	Outside	Sample Port	Yes	No	
Contact Name				Contact Phone		
Mailing Address						
Contact Signature				Date		

C. Transporter Information (optional)

Transporter			Phone			
Transporter Address						
TCEQ License #			How long have you serviced this trap?			
How Often?			Recommended Frequency			
Transporter Signature				Date		